

## SMART DND system

OMNITEC offers the hotel a modern and elegant DND system, designed to suit any style of decoration. Intuitive use; provides important extra comfort for the guest.



The **smart DND system** is widely used in hotels, motels and apartments that offer the guest the option of indicating their preferences outside the room.

The customer selects an option on the panel located inside the room, e.g. "do not disturb" or "clean room", and this is immediately displayed on the panel in the hallway. When "do not disturb" is indicated, in addition to being displayed on the outside panel, the doorbell is turned off.

The exterior panel includes a bell button, in addition to status indicators and **room number**.

**Elegant, stylish design**, with metallic frame and **backlit panel to guarantee visibility** in the dark.

**Simple to install**, it fits the standard flush-mounted boxes.

## DND GLASS system

The DND Glass system is characterised by its modern design with an exterior panel in retro glass illuminated by LED and a touch button. Its elegant finish gives the whole hall a luxurious and modern style without neglecting the comfort of the guest.

The **DND Glass system** is widely used in hotels that provide guests with the added **comfort** of being able to indicate their status on the outside of the room and prevent inappropriate interruptions.

The guest has **three options** on the interior panel: do not disturb, clean room and please wait.

Once one of these states is turned on, it is indicated immediately on the panel in the corridor. When "do not disturb" is indicated, the doorbell is turned off.

If the bell is rung and the guest cannot immediately open, pressing "wait please" will make this message appear on the outside panel for 2 minutes and the doorbell will be turned off.

In addition to the 3 status indicators and room number, the exterior panel includes a bell button.

DND Glass adapts to automated systems and message management systems to facilitate the management of the room as a whole.

Interior **panel with metal frame** and backlit panel to ensure visibility in the dark.

**Simple to install**, it fits the standard flush-mounted boxes.



Voltage: AC100 ~240V 50/60Hz | Consumption: < 5W | Panel dimensions: 86 x 86mm | Bell dimensions: 155 x 105 x 48mm

Voltage: AC100 ~240V 50/60Hz | Consumption: < 5W | External panel dimensions: 160 x 90mm  
Internal panel dimensions: 86 x 86mm | Bell dimensions: 155 x 105 x 48mm